

# BARRIER TECH®

Product Specification	Entrance Matting
Pile yarn	100% Nylon
Construction	Cut Pile
Dyeing Method	Space Dyed
Primary Backing	Colbac
Secondary Backing	Impervious Vinyl
Pile Weight	850gm/m <sup>2</sup> ±
Total Weight	3600g/m <sup>2</sup>
Pile height	7mm nominal
Total thickness	9mm nominal
Gauge	5/32"
Standard Roll	20m x 2m (approx)
Standard Matt	0.90m x 1.5m (approx)

All sizes above include borders

## Technical Specification – Overall Performance Rating

Classification	Heavy Contract
Flammability BS 4790: 1987 (1996)	Hot Metal Nut Low Radius
Flammability Onorm B3810	B1 – Q1
Colour Fastness EN 1307	Pass
Water Absorption	5.7 ltrs/m <sup>2</sup>

HIGH LIGHT FASTNESS OF COLOUR AND FIBRE OUTSTANDING ANTI-SOILING PROPERTIES

## Installation

All carpets should be fitted in accordance with BS5325: 1996.

## Recommended adhesives

For permanent bonding: Styccobond F45

**SEAMS MUST BE SEALED WITH SEAM SEALING ADHESIVE.**

## Maintenance

Barrier Tech® should be vacuumed regularly, commercial cleaning using the 'Envirodry System' or the 'Hot Water Extraction' method is recommended depending on conditions. Spot clean immediately on spill.

For further advice on maintenance contact **Simon Dickinson** on **0115 989 9210**.

**5 Year Wear Warranty Contact the office for details.**

